

M

MEDALPOWER

3.5kw

Medal Power
AC EV CHARGER



WWW.MEDAL-POWER.COM

Feature

- 8A/10A/13A/16A adjustable
- Plug and Play
- With Power/Charging/Error/Status Indicator
- Multiple safety protection include short circuit, over current, over voltage, Under-voltage, leakage, lightning, Over temperature protection.

Model Number	MPACC3.5KWGBTB
Standard	CN
Power	3.5kW
Input / Output Voltage	220VAC/220VAC
Output current	8A/10A/13A/16A adjustable
Over temperature protection	≥95°C
Rated residual operating current	TypeA
Charging mode	Plug and Play
Operating/ Storage temperature	-30°C~+50°C/-40°C~+85°C
Relative humidity	5%~95% No condensation
Life time of connector	≥10000 times
Mean time between failure	MTBF≥30000h
Metal wire sectional area	2.5mm ²
Cable length	5meters(Customizable)
Weight	3 Kg (with cable)
Color	Black/Dark Grey
1.3 inch OLED display screen	Current/Voltage/Timing/Temperature
Power Plug	GB (Standard)
Connector type	GB/T 20234.2-2015
Maximum altitude	2000m
Indicator lights	Power/Charging/Error/Status
Degree of protection	Charging Connector IP54, Host IP66
Host dimension	218*84*54.5 (mm)

LEAVE POWER FOR MEDAL POWER