

## MPI- 3000VA#24VPVT

### Features:



- High frequency inverter, lighter weight with higher efficiency
- Output power factor PF=1
- lithium battery activation start function with ac and solar mode
- Parallel function to expansion power
- Higher solar charging efficiency and battery protection
- Pure sine wave output, adaptable to different loads
- 450V high PV input
- Optional WIFI function
- Working with or without battery

## Technical Specifications

Model		MPI-3000VA#24VPVT
Input	Phase	L+N+PE
	Nominal Voltage	208/220/230/240VAC
	Voltage Range	154-264VAC±3V (Normal Mode) 185-264VAC±3V (UPS Mode)
	Frequency Range	50Hz/60Hz(Adaptive)
Output	Rated Power	<b>3000W</b>
	Output Voltage(AC)	208/220/230/240VAC±5%
	Output Frequency	50/60Hz±0.1%
	Waveform	Pure sine wave
	Transfer Time( Optional)	10ms for computer , 20ms for home appliances
	Peak power	6000VA
	Overload	Battery Mode: 1min@102%~110% Load 10s@110%~130% Load 3s@130%~150% Load 200ms@>150% Load
	Peak efficiency (battery mode)	>94%
Battery	Rated voltage	24Vdc
	Constant voltage charging voltage (Optional)	28.2Vdc
	Floating charge voltage (Optional)	27Vdc
charger	PV charging method	MPPT
	PV max input power	3500W
	MPPT tracking range	120~430Vdc
	Max PV input voltage	500Vdc
	Max PV charging current	100A
	Max AC charging current	100A
Display	LCD display	Operating mode/load/input/output, etc.
	RS232	5PIN/Pitch2.0mm, baud rate 2400
Communication port	Expansion & configuration port	2×5PIN/Pitch2.54mm, lithium battery BMS communication card, WIFI card, dry contact card, etc.
	Parallel interface	No
	Environmental parameters	Operating environment temperature
Operating environment humidity		20%~95% (Non condensing)
Storage temperature		-15~60°C
Altitude		The altitude should not exceed 1000m, derating above 1000m, up to 4000m. refer to IEC62040
noise		≤50db
Certifications		EN-IEC 60335-1, EN-IEC 60335-2-29, IEC 62109-1

LEAVE POWER FOR MEDAL POWER