

MP-LU3000VA#6B7T

Features:

1. Ultra-Small, ultra-thin personalized design, with a variety of personalized color optional.
2. Output short-circuit protection.
3. Long back up design, able to last 24 hours.
4. Battery low & high voltage protection.
5. Adopt CPU design, computer interface, have self detection function.
6. With three-level lightning protection, multi protection of your equipment.
7. No load automatic shutdown (selection).
8. Multi-function alarm.



Applications

1. PC, Terminal, Equipment.
2. Network Contact Network Equipment
3. Computer Aided teaching Equipment
4. Fax, telephone, switchboard and other communication equipment
5. Cash registers, ATM, automatic shutter door electronic equipment, medical, securities, banking and other industries.



Technical Specifications

Model	MP- LU 3000VA#6B7T
Phase	Single- Phase
Capacity	3000VA/2400W
Input	
AC Mains Input voltage	145-280VAC
Input Frequency Range	46Hz - 54Hz or 56Hz - 64Hz
Power Factor	100% load \geq 0.8
Output	
Output voltage	220 \pm 10%
voltage Range (DC Mode)	\pm 2% (\pm 10% AC Mode)
Frequency Range (Sync Calibration)	47Hz- 53Hz or 57Hz- 63Hz
Frequency Range (DC Mode)	50 Hz \pm 0.25 Hz
Surge Ratio	3: 1
Harmonic Distortion	\leq 3% THD (linear load)
Transfer Time	\leq 8ms
Waveform	Pure sine wave
Battery	
Standard Model Battery Type	12V/7AH
Standard Model Battery Quantity	6
Standard Model Charging Current	1.5A(Max)
Standard Model Charging Voltage	82.1VDC \pm 1%
Appearance	
LED Or LCD Display	Load level, battery capacity, AC Mode, battery mode, bypass mode, fault indication
Alarm	
Battery Mode	Alarm beeps every Four seconds
Low Battery	alarm beeps every second
Overload	Alarm beeps every second
Fault	Alarm beeps continuously
Environment	
Temperature and Humidity	Humidity 20-90%, temperature 0-40°C (non-condensing)
Noise (Db)	< 40dB at one-meter distance
Control Management	
Smart RS-232/USB	Support Windows® 2000/2003/XP/2008, Windows® 7/8, Linux, UNIX
Optional SNMP	Power Management supports SNMP management and network management
External Dimension	
Standard model Dimension(mm)	450*192*335mm

LEAVE POWER FOR MEDAL POWER