

Lithium-ion battery power system

MP-511000-LT

This series is a complete solution for the lithium iron phosphate battery system for the home energy storage field. There are three types of wall-mounted, vertical structures and rack. The system is safe and reliable. It can be used in home storage, industrial and commercial energy storage and other fields.

Characteristic

• Safe, reliable and long life

- Dynamic identification, automatic paralleling, no need for DIP switches
- Support Bluetooth, mobile APP switching PCS protoco
- CAN/RS485/LAN interface
- Visualization, LCD screen display
- Flexible expansion, the number of parallel machines supports up to 15
- Supports mixed parallel of old and new batteries
- Remote intelligent upgrade maintenance





 MENU ENTER DOWN





Panel silkscreen preview

CAN







OUT

Dry contact

Battery communication interface preview


System Specifications


Voltage(V)	43.2~58.4V
Cell	3.2V100Ah
Module	16S1P
Number of parallel machines	15PCS
Nominal voltage(V)	51.2
Nominal Capacity(Ah)	100
Nominal Energy(kWh)	5.12
Maximum power output(kW)	5.12
Maximum discharge current(A)	100
Maximum charging current(A)	100
Cut-off voltage(V)	40
Maximum charge voltage(V)	58.4
Cycles(25°C)	≥6000
Charging temperature(°C)	0~55
Discharge temperature(°C)	-20~55
Operating humidity	<95%R.H
Communication mode	CAN/RS485
Dry contact Customize	ed by demand
Optional modules Bluetoot	th, 4G module
Product size(W*D*H,mm)	430*442*177
Packing size(W*D*H,mm)	535*527*290
Protection class	IP21
System weight(kg)	Approx 48
Certification IEC62619/U	JN38.3/MSDS


Product renderings




Cell characteristic curve









With process improvements and product upgrades, the product parameters are subject to change without prior notice

Version: 202307