

## MP-LU1200VA#2B9T

### Features:

---

- >> Simple, compact and generous machine appearance
- >> Super wide mains input range
- >> Excellent microprocessor to ensure reliable operation
- >> Automatic adjustment of the AC mains power boost, step-down, stable voltage output
- >> Mains restart function
- >> Output modified sine wave
- >> Automatic charge in off-mode
- >> Cold start function
- >> Compatible generators



### Applications

---

PC/Fax/Modem  
Small server/Lan  
Cash-counting  
Attendance machine  
Miniature Terminal Equipment  
SOHO Equipment



LEAVE POWER FOR MEDAL POWER

## Technical Specifications

<b>Model</b>	MP-LU1200VA#2B9T
Capacity	1200VA/720W
<b>Input</b>	
Voltage	220VAC
AC Mains Input voltage Range	145-280 VAC (same as AC mains)
Frequency	50 Hz
<b>Output</b>	
voltage Range (Battery Mode)	±10%
Frequency Range (Battery Mode)	50 Hz ±1 Hz
Transfer Time	<6ms
Waveform (Battery)	Modified sine wave
<b>Battery</b>	
Battery Type &Quantity	12V 9Ah x 2
Battery Charging Time	6 hours charge to 90%
<b>LED Indicators</b>	
AC Mode	Green light
Battery Mode	Red light flash
<b>Audible Alarm</b>	
Battery Mode	Alarm beeps every six seconds
Low Battery	alarm beeps every second
Overload	Alarm beeps twice every second
Fault	Alarm beeps continuously
<b>Protection Function</b>	
Comprehensive Protection	Overload, deep discharge and over-charge protection
<b>Environment</b>	
Temperature and Humidity	Relative humidity 0-90% and temperature 0- 40°C (No-condensing)
Noise	less than 40dB at one-meter distance
<b>Physical Function</b>	
Dimensions D X W X H (mm)	403*223*295
Net Weight (kgs)	9.1

LEAVE POWER FOR MEDAL POWER