



MEDALPOWER

3.6kw

**Medal Power
AC EV CHARGER**



WWW.MEDAL-POWER.COM

Feature

- 8A/10A/13A/16A adjustable
- Plug and Play
- With Power/Charging/Error/Status Indicator
- Multiple safety protection include short circuit, over current, over voltage, Under-voltage , leakage , lightning ,Over temperature protection.

Specifications

| | |
|----------------------------------|----------------------------------|
| Power | 3.6KW |
| Input/Output | 230VAC/230VAC |
| Output current | 8A/10A/13A/16A adjustable |
| Over temperature protection | ≥95°C |
| Rated residual operating current | AC30mA+DC6mA |
| Operating temperature | '-30°C- +50°C |
| Storage temperature | '-40°C- +85°C |
| Relative humidity | 5%~95% No condensation |
| Life time of connector | ≥10000 times |
| Mean time between failure | MTBF≥8796h |
| Metal wire sectional area | 2.5mm ² |
| Maximum altitude | 2000m |
| Connector type | IEC 62196-2 Type 2 |
| Cable length | 5 meters (Customizable) |
| Weight | 3 Kg (with cable) |
| Indicator lights | Power/Charging/Fault/Current |
| Protection | Connector IP54, Host IP66 & IK10 |
| Host dimension | 186*82*42(mm) |

LEAVE POWER FOR MEDAL POWER